

LMWB04, 06

CATALOGUE 2024-25



Digital Water Bath

LMWB04, 06

SALIENT FEATURES

- It adopts new design structure, which could avoid the leakage of steam.
- There are pointer type temperature controller and intellectual type temperature controller for selecting. The intellectual temperature controller has high lightness digital display and key operating button, which is easy to operate. It has high precision on controlling the temperature.

Thermostatic Water Baths Uses Evaporating, drying, concentrating and thermostatically heating. Widely adopted in medical and research units factories, universities, chemical dyeing and petroleum



E - Catalogue

HSN Code : 84192090

SPECIFICATIONS	Model	LMWB04	LMWB06
	Column	2 rows 4 holes	
Make	LABMAN		
Temp. range	Rt+5~100°C		
Temp. Resolution Ratio	0.1°C		
Temp. Accuracy	±0.5°C		
Temp. Uniformity	±1°C		
Water sink	Stainless steel, surface electrolysis treatment		
Outer shell	Cold rolled steel plate, surface electrostatic powder spray		
Heater	Stainless steel U type heating tube		
Temp. control mode	PID		
Timer	0∞999 min (with timing function)		
Timing function	Fixed temperature operation, timing function, auto stop.		
Program	Optional: multi-section program control		
Additional function	Deviation correction, menu key lock, power failure back-up, power-off parameter memory, PID adjustable		
Sensor	Thermal resistor		
Safety device	Over-temperature alarm, short-circuit protection		
Power rating	800W	1200W	
Inner Chamber size(WxLxH)mm	305x305x135	470x305x130	
Packing size (WxLxH) (mm)	405x405x250	565x405x250	
Internal volume (approx.)	12L	18L	
Cover aperture	Ø120mm		
Cover Rings per hole	5		
Power Supply	Adaptor, Using AC 220V, 50/60Hz		
Weight	6.5kg	8kg	

★ Specifications are subject to change without notice.

STANDARD ACCESSORIES : Main Instrument, ABS Beaker Holder, Aluminium Heater Cover, Test Certificate