

PCR9602G

CATALOGUE 2024-25



Polymerase Chain Reaction



Touch Screen Gradient Thermal Cycler - PCR9602G



Polymerase Chain Reaction (PCR) is widely used in Molecular biology. As PCR progresses, the DNA thus generated is itself used as a template for replication. With PCR it is possible to amplify a single or few copies of a specific DNA fragment across several orders of magnitude, generating millions of copies of the DNA fragments.

SALIENT FEATURES

- Advanced technologies, WINDOWS operating system.
- Automatic restart after power failure.
- Each thermal block has 4 independent temperature control sensors and 8 peltier heating units to ensure accurate and uniform temperature across block surface, and provide users with replicating previous condition set-up.
- 8" TFT color touch-screen with graphical display provides easy use for setting up and monitoring set parameter.
- The actual and target temperatures can be viewed and displayed graphically in real time.
- Built-in 11 standard program file template, can quickly edit the required files.
- Internal flash memory for 10000 typical PCR files in free configurable folders.
- Compatible with mouse, keyboard, capable to transfer data and perform software updates via USB Drive.
- Applicable with the following 0.2ml tube models: non-skirted, semi and fully skirted plated.
- Replaceable module, dual-block module can simultaneously run two different PCR programs.

Temperature °C

Gradient °C



STANDARD ACCESSORIES : Main instrument, Touch pen, Power Cable, Test Certificate

PCR9602G

CATALOGUE 2024-25

**Gradient Thermal Cycler PCR**

HSN Code : 90275090

MODEL	PCR9602G
Capacity	96×0.2ml
Make	LABMAN
Temperature Range	0 ~ 100°C
Max. Heating Rate	5°C/s
Max. Cooling Rate	4°C/s
Uniformity & Accuracy	±0.1°C
Display Resolution	0.1°C
Temperature Control	Block / Tube
Ramping Rate Adjustable	0.1°C ~ 5°C
Gradient Uniformity	±0.2°C
Gradient Accuracy	±0.2°C
Gradient Temp. Range	30°C ~ 100°C
Gradient Spread	1°C ~ 30°C
Hot Lid Temperature	30°C ~ 110°C
Hot Lid Height Adjustable	Stepless adjustable
Number of Programs	10000 +(USB FLASH)
Max. No. of Step	30
Max. No. of Cycle	99
Time Increment/Decrement	1 Sec ~ 9 Min 59 Sec
Temp. Increment/Decrement	0.1°C ~ 9.9°C
Pause Function	Yes
Auto Data Protection	Yes
Hold at 4°C	Forever
Print, LAN to computer,	Yes
LCD display	Touch Screen, 8inch, 800×600 Pixels, TFT
Communication	USB2.0 , LAN
Power Supply	85 ~ 264VAC , 47 ~ 63Hz , 600 W
Dimension (L×W×H) & Weight	380 × 240 × 260 mm & 9 kg

SPECIFICATIONS

★ Specifications are subject to change without notice.

Please use PCR9602G with stabilizer for better results & Long Life