

RCB620T

CATALOGUE 2024-25

**SALIENT FEATURES**

- ✦ Touchscreen Display, Horizontal Design
- ✦ Specialized Model to attach Viscometer on Top
- ✦ PT100 temperature sensor.
- ✦ Both sides folding handle for easy movement
- ✦ Overheat protection, PID temperature control system
- ✦ Stainless steel inner tank, Waterlevel alarm function
- ✦ Fast cooling, low noise, low vibration, stable and reliable performance
- ✦ Pump flow rate 6L/min. & Programmable temperature controller

- **Application** : To maintain the temperature, it can be attached in below instruments.
 - Viscometer
 - Polarimeter
 - Electrophoresis System
 - Rotary Evaporator
 - Spectrophotometer
 - Refractometer
 - Fermentation tank
 - Chromatographic Column

Touchscreen - Horizontal Design
Refrigerated Circulating Bath

RCB620T

HSN Code : 84198990



E - Catalogue

Liquid to be used : 5°C and below - Alcohol, 5°C ~85°C, - Pure Water, 85°C ~95°C - 15% Glycerin water solution

SPECIFICATIONS

MODEL	RCB620T
Make	LABMAN
Shape	Horizontal (Specialized for Viscometer)
Temperature Range	-20°C to 100°C
Temperature Display resolution	0.01°C
Temperature Accuracy	± 0.05°C
Temperature Control	Microprocessor PID
Display	Touchscreen
Refrigeration	Air Cooled refrigeration through compressor
Refrigerant	R-134A
Pump circulation	Internal & External
Temperature sensor	PT100
Pump flow rate	6L / min
Bath Tank capacity	6L
Tank size (LxWxD)	350 x 165 x 130mm
Bath Opening & Bath depth	110 mm dia & 130mm
Power Requirements	Adaptor, Using AC 220V,50/60Hz
Packing Dimensions (LxWxH)	540 x 470 x 550 mm
Net Weight / Gross Weight	27kg / 30 kg

STANDARD ACCESSORIES : Main Instrument, SS-Lid, Circulating Tube, Test Certificate

★ Specifications are subject to change without notice.